


# Jig git commands

Reference for ozwala jig push, release, set, update, install, pin, unpin, versions, info and ozwala git-token.

development · 2026-11-22

# Jig git commands

See Your jig in git for how these fit together.

| Command | Does |
| --- | --- |
| `ozwala jig set <name> [--url U] [--provider github\|gitlab\|other] [--api URL] [--token-stdin \| --clear-token] [--host-token] [--auto-update on\|off] [--follow releases\|commits]` | Changes a jig's git settings. A token is read from a prompt or standard input, never an argument; `--host-token` saves it for the repository's host instead of the jig. |
| `ozwala jig push <name> [-m M] [--url U] [--create [--public] [--owner O] [--repo R]] [--request [--title T] [--branch B]] [--author "Name <email>"] [--yes]` | Commits everything in the jig and pushes it. `--create` makes a new private GitHub or GitLab repository first. `--request` proposes the change on a branch with a pull or merge request; while one is open, a plain push adds to it. `--yes` answers the public-repository question. |
| `ozwala jig release <name> [--bump patch\|minor\|major \| --version X.Y.Z] [--notes N]` | Writes the version into `jig.yml`, commits, tags `vX.Y.Z`, pushes, and on GitHub and GitLab makes a release page. |
| `ozwala jig install <url> [--token-stdin] [--no-save-token]` | Installs from a git URL (https, `ssh://` or `git@host:path`, with an optional `@version`), a directory or a `.zip`, and syncs its skills. A private repository asks for a token and saves it for the host. |
| `ozwala jig update <name> \| --all [--discard] [--force]` | Moves a jig to its pin, else its newest release, else its latest commit, and re-syncs its skills. Refuses to lose changes unless `--discard` (which asks; `--force` doesn't). |
| `ozwala jig pin <name> <version>` / `ozwala jig unpin <name>` | Holds a jig at a version / follows releases again. Pinning turns auto-update off for the jig. |
| `ozwala jig versions <name>` | Lists the repository's tags, newest first. |
| `ozwala jig info <name>` | Also shows the service, what updates follow, auto-update, where the token comes from (never the token), changes on this machine, an open proposal, and the last automatic check. |

| Command | Does |
| --- | --- |
| `ozwala git-token set <host> [--stdin]` / `clear <host>` / `list` | Tokens for a host, used by every jig there that has none of its own. `list` never shows a token. |

Configuration keys: `provider`, `api`, `auto_update`, `follow` and `proposal` on each jig, and `auto_update` at the top of `config.yml`. Tokens live in `credentials.yml`, never in `config.yml`.